

Pedestrian lowlifter truck 1,3 ton

BT tyro

LHE130



Pedestrian lowlifter truck

Truck specifications					LHE130
Identification	1.2	Model			LHE130
	1.3	Drive			Electric
	1.4	Operator type			Pedestrian
	1.5	Load capacity/rated load	Q	kg	1300
	1.6	Load centre	c	mm	600
	1.8	Load distance, center of drive axle to fork	x	mm	947
	1.9	Wheelbase	y	mm	1185
Weight	2.1	Service weight including battery		kg	135
	2.2	Axle load, with load, drive/castor/fork wheel		kg	500/ /1123
	2.3	Axle load, without load, drive/castor/fork wheel		kg	96/ /26
Wheels	3.1	Drive/castor/fork wheel			Polyurethane
	3.2	Wheel size, front	Ø x width	mm	210x70
	3.3	Wheel size, rear	Ø x width	mm	80x70
	3.4	Additional wheels, dimensions	Ø x width	mm	80x30
	3.5	Wheels, number front/rear (x = driven wheels)			1x-4
	3.6	Track width, front	b ₁₀	mm	420
	3.7	Track width, rear	b ₁₁	mm	380
Dimensions	4.4	Lift	h ₃	mm	115
		Lift height	h ₂₃	mm	195
	4.9	Height of tiller in drive position, min./max.	h ₁₄	mm	700/1160
	4.15	Height, fork lowered	h ₁₃	mm	80
	4.19	Overall length	l ₁	mm	1530
	4.20	Length to face of forks	l ₂	mm	380
	4.21	Overall width	b ₁	mm	540
	4.22	Fork dimensions	s/e/l	mm	47/160/1150
	4.25	Width over forks	b ₅	mm	540
	4.32	Ground clearance, center of wheelbase	m ₂	mm	33
	4.34.1	Aisle width for pallets 1000x1200 crossways	A _{st}	mm	
4.34.2	Aisle width for pallets 800x1200 lengthways	A _{st}	mm	2000	
4.35	Turning radius	Wa	mm	1330	
Performance	5.1	Travel speed, with/without load		km/h	4,6/4,8
	5.2	Lift speed, with/without load		m/s	0,020/0,025
	5.3	Lowering speed, with/without load		m/s	0,05/0,04
	5.8	Max. gradeability, with/without load		%	4/16
	5.10	Service brake			Electromagnetic
Electric motor	6.1	Drive motor rating S2 60 min		kW	0,65
	6.2	Lift motor rating at S3 15%		kW	0,50
	6.4	Battery voltage/nominal capacity K5		V/Ah	24/36
	6.5	Battery weight		kg	7
	6.6	Energy consumption acc. to VDI cycle		kWh/h	0,18
	Other	8.1	Type of drive control		
8.4		Sound level at the driver's ear according to DIN 12 053		dB (A)	<70

All data are based on table configuration. Other configurations may give other values.

Truck performance and dimensions are nominal and subject to tolerances.

Toyota Material Handling products and specifications are subject to change without notice.

